



GEARS

PRECISION BORE MACHINING SYSTEMS & SOLUTIONS



WHEN IT COMES TO HONING GEARS, SUNNEN DELIVERS.

MORE MACHINES | MORE TOOLING | MORE ABRASIVES | MORE HONING FLUIDS | MORE GAGING | MORE FIXTURING | MORE AUTOMATION | MORE PRECISION | MORE CHOICES



With over 80 years of technological leadership, Sunnen has *the* solution for the precision honing of gears. Our advanced, precision bore machining technology:

- Provides improved process control and greater accuracy, resulting in gear drives that run smoother, quieter, and more efficiently
- Delivers improved bore geometry in the gear blank, resulting in a higher quality finished gear
- Results in fewer burrs in bores and keyways, providing more accurate location on hobbing arbors
- Creates a crosshatch surface finish that permits better oil retention in rotating gears for longer life

We can provide a system for virtually any gear honing application, including:

- Gears of all types, including helical, pinion, worm, spline, sprocket, and spur
- Virtually any material from powdered metal to hardened steel
- Gears with keyways and cross holes
- A wide range of bore diameters, lengths, and surface finishes

Only Sunnen offers all three types of honing technologies – conventional, single-pass or KROSSGRINDING®. We also offer the industry's largest choice of machines – horizontal or vertical, single or multi-spindle, automated or manual, standard or customized – so no matter what you require, we have the Sunnen solution.

SUNNEN PROVIDES GLOBAL SUPPORT

Sunnen's worldwide sales and service team provides comprehensive support for the installation and operation of every system we make. To find the Sunnen representative nearest you, visit our website:
www.sunnen.com






SV-1000 SERIES
VERTICAL HONING MACHINES

The SV-1000 Series is capable of holding the industry's tightest production environment tolerances – as fine as 0,00025 mm (0.00010 inch) – tolerances far superior to I.D. grinding.

Built on a proven, modular platform, the SV-1000 Series can be easily customized and automated to suit your exact specifications – whatever your needs demand, from multiple spindles to air gaging. Plus, this flexible system supports both single-pass and conventional reciprocating honing. Brushing stations can also be added.

Perfect for mid- to high-production manufacturers, the SV-1000 Series delivers the lowest cost per honed part with the tight bore tolerances you expect from Sunnen.

BORE DIAMETER RANGE (I.D.):
3 mm – 65 mm
(.118 inch – 2.56 inch)*




VSS® SERIES 2
SINGLE STROKE® HONING SYSTEM

The VSS-2 is a value-priced single-pass honing machine that delivers precise bore size, geometry and surface finish. It is very easy to set up and operate and is the most productive machine in its class.

An advanced spindle design and multiple spindle configurations (up to six) make the VSS-2 a versatile solution for just about any production environment. And the system's PLC control with Sunnen software makes operation easier and provides more feed, speed and special cycle options to satisfy a wider range of applications.

The system is the perfect solution for mid- to high-production applications that are suited to single-pass bore sizing.

BORE DIAMETER RANGE (I.D.):
4 mm – 65 mm
(.156 inch to 2.56 inch)*



KGM™ -5000
KROSSGRINDING® SYSTEM


Sunnen's KGM-5000 KROSSGRINDING System sets the industry standard for precision size control and bore geometry in a horizontal spindle system.

No other mid- to high-production horizontal spindle honing system on the market can match the precision roundness, straightness, bore size, and finish capabilities of the KGM-5000. The system is able to hold production environment tolerances as fine as 0,00025 mm (0.00010 inch).

The menu-driven Windows® operating system makes set up and operation easy – even for unskilled operators. Separate set-ups can be entered and saved for future production runs, saving time and money in the process.

High precision combined with ease of use. The KGM-5000 KROSSGRINDING System is a field-proven, profit-producing fit for virtually any shop.

BORE DIAMETER RANGES (I.D.):
3 mm – 65 mm
(.118 inch – 2.56 inch)*



ML-5000
AUTOMATIC HONING MACHINE

The Sunnen ML-5000 horizontal power stroked honing machine is up to six times faster than I.D. grinding and can be set up in half the time. The fast stock removal rates of the ML-5000 also allow the elimination of preliminary reaming, boring or grinding on many jobs.

Programmable stroke control virtually eliminates taper by allowing the honing tool to dwell or short stroke at either end of the bore. Cycle time control delivers increased productivity and consistency by automatically adjusting feed pressure to optimize abrasive performance.

The ML-5000 delivers optimum bore geometry and produces a desirable oil-bearing crosshatch finish, and can be automated for mid- to high-production applications.

BORE DIAMETER RANGES (I.D.):
1,5 mm - 165,1 mm
(.060 inch - 6.500 inch)*



*OTHER SIZES AVAILABLE UPON REVIEW.



CUSTOM, HIGH-PRODUCTION VERTICAL HONING SYSTEMS

Since 1924, Sunnen has defined the state of the art in the industry, and our current generation of high precision honing systems represents the very finest solutions available anywhere in the world. Sunnen systems are reliable, durable, and flexible and are designed to deliver the precision our customers have grown to expect.

From design to delivery, you have the Sunnen commitment to service and quality. Our technical experts will work with you to create a complete solution to fit your exact

requirements, including the machine model, number of spindles, style of tooling, fixture design, abrasives selection, automation and gaging packages, and any other platform customization you may require.

After your system is built, we'll set up a live run-off demonstration at our facility. Once it meets all specifications, we'll commission your system and train your staff.



"BECAUSE OF THEIR VERSATILE DESIGN, WE CAN CUSTOMIZE AND AUTOMATE MANY OF OUR SYSTEMS TO MEET YOUR SPECIALIZED GEAR COMPONENT HONING REQUIREMENTS. JUST CONTACT YOUR SUNNEN REPRESENTATIVE FOR A FREE NEEDS ANALYSIS TO GET THE DESIGN PROCESS STARTED."

TOOLING

Sunnen offers an extensive line of tooling that delivers precise, accurate and consistent bore sizing of gear components. Tooling choices include diamond or CBN multi-stone tools and vitrified abrasive tools.

CGT TOOLS

KROSSGRINDING® Plated Diamond Tools
High-precision, plated diamond tools deliver extreme accuracy, excellent stock removal capability and long life (tool wear is next to zero per cycle). These tools hold tolerances to within 0,00025 mm (0.000010 in), even in a production environment.

MMT MULTI-STONE MANDRELS

These mandrels offer faster cycle times, superior accuracy, longer time between stone changeovers, and maintain superior bore geometry.
ABRASIVE SELECTION: METAL BOND CBN OR DIAMOND ABRASIVES

SINGLE STROKE® HONING TOOLS

Sunnen's line of Single Stroke® Honing tools provide fast stock removal and consistent bore geometry. With our new generation of HPH (High Production Helix) plated diamond single-pass honing tools, you can size thousands of bores with the same tool, reducing your production costs.

STANDARD MANDRELS

For bores under 150 mm (6 inch) in diameter, the industry-standard Sunnen mandrels provide straightness and roundness with minimum stock removal. Standard mandrels can be supplied for blind hole honing, with multiple stones for honing long bores.

BORE DIAMETER RANGE:

3 mm - 32 mm
(.118 inch - 1.20 inch)*

CUSTOM-DESIGNED FOR YOUR SPECIFIC APPLICATION

BORE DIAMETER RANGE:

4 mm - 52,2 mm
(.156 inch - 2.055 inch)*

BORE DIAMETER RANGE:

1,5 mm - 165 mm
(.06 inch - 6.5 inch)*

SUNNEN-MADE ABRASIVES & LUBRICANTS

From aluminum oxide to silicon carbide to diamond and CBN, Sunnen offers the industry's largest variety of mounted or un-mounted stick abrasives, bond types, grain sizes and stone configurations.

Before any stone is shipped, it is graded and qualified, maintaining the most exacting quality control standards in the industry to assure you of the most precise honing performance available.

Sunnen offers the right honing oil or waterbase coolant for virtually any honing application. The use of Sunnen's premium line of lubricants will help produce the lowest overall honing cost per part.

* OTHER SIZES AVAILABLE UPON REVIEW.



A LEGACY OF EXCELLENCE SINCE 1924.

WORLDWIDE

Our global manufacturing, distribution, and sales and service network allows us to deliver quality Sunnen solutions worldwide.

And our state-of-the-art Technical Services Centers allow our technical experts to develop innovative solutions to customer application challenges. The Centers also provide answers for customer questions and training for Sunnen representatives around the world.

SUNNEN PRODUCTS COMPANY

World Headquarters
St. Louis, MO – USA
Phone 1.314.781.2100
Fax 1.314.781.2268
Toll Free 1.800.325.3670
Email sunnen@sunnen.com
www.sunnen.com

SWITZERLAND – SUNNEN AG

Phone +41 71 649 33 33
Fax +41 71 649 33 34
Email info@sunnen.ch
www.sunnen.ch

ITALY – SUNNEN ITALIA S.R.L.

Phone +39 02 383 417 1
Fax +39 02 383 417 50
Email sunnen@sunnenitalia.com
www.sunnenitalia.com

FRANCE – SUNNEN SAS

Phone +33 01 69 30 0000
Fax +33 01 69 30 1111
Email info@sunnen.fr
www.sunnen.fr

UK – SUNNEN PRODUCTS LTD.

Phone +44 1442 39 39 39
Fax +44 1442 39 12 12
Email hemel@sunnen.co.uk
www.sunnen.co.uk

POLAND – SUNNEN POLSKA SP. Z O.O.

Phone +48 22 814 34 29
Fax +48 22 814 34 28
Email sunnen@sunnen.pl
www.sunnen.pl

RUSSIA – SUNNEN RUS

Phone +7 495 258 43 43
Fax +7 495 258 91 75
Email sunnen@sunnen-russia.ru
www.sunnen.ru

CZECH REPUBLIC – SUNNEN S.R.O.

Phone +420 383 376 317
Fax +420 383 376 316
Email sunnen@sunnen.cz
www.sunnen.cz

CHINA – SHANGHAI SUNNEN MECHANICAL CO. LTD.

Phone +86 21 5813 3990
Fax +86 21 5813 2299
Email shsunnen@sunnensh.com
www.sunnensh.com



Sunnen reserves the right to change or revise specifications and product design in connection with any feature of our products contained herein. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment, supplies or accessories previously sold. Information contained herein is considered to be accurate based on available information at the time of printing. Should any discrepancy of information arise, Sunnen recommends that user verify the discrepancy with Sunnen before proceeding.